

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 6.7 Revision Date 18.12.2024 Print Date 30.04.2025

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Vinyl acetate

Product Number : 48486
Brand : Supelco
Index-No. : 607-023-00-0

REACH No. : 01-2119471301-50-XXXX

CAS-No. : 108-05-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3

CHEMIKART

1.4 Emergency telephone

Emergency Phone # : 000 800 1007 141 (CHEMTREC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flammable liquids, (Category 2) H225: Highly flammable liquid and vapor.

Acute toxicity, (Category 4) H332: Harmful if inhaled.

Carcinogenicity, (Category 2) H351: Suspected of causing cancer.

Specific target organ toxicity - single exposure, (Category 3),

Respiratory system

H335: May cause respiratory irritation.

Long-term (chronic) aquatic

hazard, (Category 3)

H412: Harmful to aquatic life with long

lasting effects.

Supelco- 48486 Page 1 of 12

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P202 Do not handle until all safety precautions have been read and

understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P233 Keep container tightly closed.
P273 Avoid release to the environment.

for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Supplemental Hazard

Statements

none

Reduced Labeling (<= 125 ml)

Pictogram

Signal Word Danger

Hazard Statements

H351 Suspected of causing cancer.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P202 Do not handle until all safety precautions have been read and

understood.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Supplemental Hazard

Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

Supelco- 48486 Page 2 of 12

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Acetoxyethylene

Component		Classification	Concentration
vinyl acetate			
CAS-No. EC-No. Index-No.	108-05-4 203-545-4 607-023-00-0	Flam. Liq. 2; Acute Tox. 4; Carc. 2; STOT SE 3; Aquatic Chronic 3; H225, H332, H351, H335, H412	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

Supelco- 48486 Page 3 of 12

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Flash back possible over considerable distance., Container explosion may occur under fire conditions.

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Supelco- 48486 Page 4 of 12

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0,7 mm Break through time: 240 min

Material tested:Butoject® (KCL 898)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

Supelco- 48486 Page 5 of 12

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state clear, liquidb) Color colorlessc) Odor fruity

d) Melting point/ range: -93 °C

point/freezing point

e) Initial boiling point 72 - 73 °C and boiling range

f) Flammability (solid, No data available

gas)

g) Upper/lower Upper explosion limit: 13,4 %(V) flammability or explosive limits Upper explosion limit: 2,6 %(V)

h) Flash point -8 °C - closed cup - closed cup

i) Autoignition 402 °C at 1.013 hPa
 j) Decomposition No data available

temperature

k) pH No data available

I) Viscosity Viscosity, kinematic: No data available

Viscosity, dynamic: No data available

m) Water solubility 20 g/l at 20 °C - completely soluble

n) Partition coefficient: log Pow: 0,73 at 25 °C - Bioaccumulation is not expected.

n-octanol/water

o) Vapor pressure 113 hPa at 20 °C

p) Density 0,934 g/mL at 25 °C

Relative density No data available q) Relative vapor No data available

density

r) Particle No data available

characteristics

s) Explosive properties Not classified as explosive.

t) Oxidizing properties none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Supelco- 48486 Page 6 of 12

10.3 Possibility of hazardous reactions

Unstable upon depletion of inhibitor.

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 2.900 mg/kg

Remarks: (RTECS)

Symptoms: Gastrointestinal disturbance, Risk of aspiration upon vomiting., Pulmonary

failure possible after aspiration of vomit.

LC50 Inhalation - Rat - 4 h - 11,4 mg/l - vapor

Remarks: (RTECS)

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of

respiratory tract

LD50 Dermal - Rabbit - male - 7.440 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Remarks: Drying-out effect resulting in rough and chapped skin.

Possible damages: slight irritation

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Human lymphocytes

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 473

Supelco- 48486 Page 7 of 12

Result: positive

Test Type: Micronucleus test

Test system: human lymphoblastoid cells

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 487

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: human lymphoblastoid cells

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 490

Result: positive

Test Type: Genotoxicity in vivo

Species: Mouse Cell type: sperm

Application Route: Intraperitoneal

Result: negative Remarks: (ECHA)

Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal Method: OECD Test Guideline 474

Result: Positive results were obtained in some in vivo tests.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain

components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Repeated dose toxicity - Mouse - female - Oral - 3 Months - NOAEL (No observed adverse effect level) - 281 mg/kg

RTECS: AK0875000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Supelco- 48486 Page 8 of 12

After uptake:

Systemic effects:

Dizziness somnolence Unconsciousness

Absorption can result in damage to:

Liver Kidney

Effect potentiated by: ethanol

This substance should be handled with particular care.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to daphnia and other aquatic invertebrates

static test EC50 - Daphnia magna (Water flea) - 12,6 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae ErC50 - Pseudokirchneriella subcapitata - 12,7 mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to flow-through test NOEC - Pimephales promelas (fathead minnow) -

fish(Chronic toxicity) 0,55 mg/l - 34 d

(OECD Test Guideline 210)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 14 d

Result: 82 - 98 % - Readily biodegradable.

(OECD Test Guideline 301C)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Supelco- 48486 Page 9 of 12

12.7 Other adverse effects

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1301 IMDG: 1301 IATA: 1301

14.2 UN proper shipping name

ADR/RID: VINYL ACETATE, STABILIZED IMDG: VINYL ACETATE, STABILIZED IATA: Vinyl acetate, stabilized

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

Tunnel restriction code : (D/E)

Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

National legislation

Seveso III: Directive 2012/18/EU of the P5c FLAMMABLE LIQUIDS European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Supelco- 48486 Page 10 of 12

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements

H225	Highly flammable liquid and vapor.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM -American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. -Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact

Supelco- 48486 Page 11 of 12

with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.



Supelco- 48486 Page 12 of 12