

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 6.8 Revision Date 30.12.2023 Print Date 04.05.2025

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : o-Phenylenediamine

Product Number : P5412 Brand : Sigma

Index-No. : 612-145-00-2

REACH No. : This product is a mixture. REACH Registration Number see

section 3.

CAS-No. : 95-54-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

Uses advised against : For R&D use only. Not for pharmaceutical, household or other

uses

1.3

1.4 Emergency telephone

Emergency Phone # : 000 800 1007 141 (CHEMTREC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Acute toxicity, (Category 3) H301: Toxic if swallowed.

Eye irritation, (Category 2) H319: Causes serious eye irritation.

Skin sensitization, (Category 1) H317: May cause an allergic skin reaction.

Sigma- P5412 Page 1 of 14

Germ cell mutagenicity, H341: Suspected of causing genetic (Category 2) defects.

Carcinogenicity, (Category 2) H351: Suspected of causing cancer.

Short-term (acute) aquatic hazard, (Category 1)

H400: Very toxic to aquatic life.

Long-term (chronic) aquatic

H410: Very toxic to aquatic life with long

hazard, (Category 1) lasting effects.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word	Danger
Hazard Statements H301 H317 H319 H341 H351 H410	Toxic if swallowed. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing genetic defects. Suspected of causing cancer. Very toxic to aquatic life with long lasting effects.
Precautionary Statements P202 P273 P280	Do not handle until all safety precautions have been read and understood. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310 P302 + P352 P305 + P351 + P338	IF SWALLOWED: Immediately call a POISON CENTER/ doctor. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard

Reduced Labeling (<= 125 ml)
Pictogram

Statements

Signal Word	Danger
Hazard Statements	
H301	Toxic if swallowed.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.

none

Sigma- P5412 Page 2 of 14

Precautionary Statements

P202 Do not handle until all safety precautions have been read and

understood.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302 + P352 IF ON SKIN: Wash with plenty of water.

Supplemental Hazard

Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms : OPD

1,2-Diaminobenzene 1,2-Phenylenediamine

Formula : $C_6H_8N_2$ Molecular weight : 108,14 g/mol

Component		Classification	Concentration
o-phenylenediamii	ne		
CAS-No. EC-No. Index-No.	95-54-5 202-430-6 612-028-00-6 *	Acute Tox. 3; Acute Tox. 4; Eye Irrit. 2; Skin Sens. 1; Muta. 2; Carc. 2; Aquatic Acute 1; Aquatic Chronic 1; H301, H332, H312, H319, H317, H341, H351, H400, H410 M-Factor - Aquatic Acute: 1 - Aquatic Chronic: 1	>= 50 - < 70 %

^{*}A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

Sigma- P5412 Page 3 of 14

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Nitrogen oxides (NOx)

Mixture with combustible ingredients.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Sigma- P5412 Page 4 of 14

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage stabilityRecommended storage temperature

2 - 8 °C

Moisture sensitive. Store under nitrogen. May darken on storage

Storage class

Storage class (TRGS 510): 6.1C: Combustible, acute toxic Cat.3 / toxic compounds or compounds which causing chronic effects

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Sigma- P5412 Page 5 of 14

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: > 480 min

Material tested: Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: > 480 min

Material tested:

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

protective clothing

Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type P3

Sigma- P5412 Page 6 of 14

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state tabletb) Color white, tan

c) Odor No data available

d) Melting point/range: 100 - 102 °C

point/freezing point

e) Initial boiling point 256 - 258 °C and boiling range

f) Flammability (solid, No data available gas)

g) Upper/lower Lower explosion limit: 1,5 %(V) flammability or explosive limits

h) Flash point 136 °C - closed cupi) Autoignition No data available temperature

j) Decomposition No data available temperature

k) pH 8,7

I) Viscosity Viscosity, kinematic: No data available Viscosity, dynamic: No data available

m) Water solubility 39,3 g/l at 20 °C - OECD Test Guideline 105

n) Partition coefficient: log Pow: 0,12 at 25 °C - OECD Test Guideline 107 n-octanol/water

o) Vapor pressure 3,27 hPa at 100 °C

0,01 hPa at 25 °C

0,001 hPa at 20 °C - OECD Test Guideline 104

p) Density 1,030 g/cm3

Relative density No data available
q) Relative vapor No data available density

r) Particle No data available

characteristics

Sigma- P5412 Page 7 of 14

s) Explosive properties No data available

t) Oxidizing properties No data available

9.2 Other safety information

Bulk density 0,74 g/cm3 at 24 °C

SECTION 10: Stability and reactivity

10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Acute toxicity estimate Oral - 195,85 mg/kg

(Calculation method)

Acute toxicity estimate Inhalation - 4 h - > 5 mg/l - dust/mist(Calculation method)

Symptoms: Possible symptoms:, mucosal irritations Acute toxicity estimate Dermal - > 2.000 mg/kg

(Calculation method)

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye irritation.

Sigma- P5412 Page 8 of 14

Respiratory or skin sensitization

Mixture may cause an allergic skin reaction.

Germ cell mutagenicity

Evidence of genetic defects.

Carcinogenicity

Evidence of a carcinogenic effect.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Endocrine disrupting properties

Product:

The substance/mixture does not contain Assessment

components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Components

o-phenylenediamine

Acute toxicity

Acute toxicity estimate Oral - 100,1 mg/kg

(Expert judgment)

Remarks: (Regulation (EC) No 1272/2008, Annex VI) LC50 Inhalation - Rat - male - 4 h - 3,6 mg/l - dust/mist Remarks: (Regulation (EC) No 1272/2008, Annex VI)

Acute toxicity estimate Dermal - 1.100,1 mg/kg

(Expert judgment)

Remarks: (Regulation (EC) No 1272/2008, Annex VI)

LDLo Dermal - Rabbit - 1.500 mg/kg

Remarks: (RTECS)

Sigma- P5412 Page 9 of 14

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation - 72 h (OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: May cause sensitization by skin contact.

Germ cell mutagenicity

In vitro tests showed mutagenic effects

Test Type: Ames test

Test system: Salmonella typhimurium

Result: positive Species: Guinea pig Result: positive Remarks: (ECHA)

Carcinogenicity

Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Sigma- P5412 Page 10 of 14

12.6 Endocrine disrupting properties **Product**:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

Components

o-phenylenediamine

Toxicity to fish flow-through test LC50 - Oncorhynchus mykiss (rainbow trout)

- 42,9 mg/l - 96 h Remarks: (ECHA)

Toxicity to daphnia and other aquatic

semi-static test EC50 - Daphnia magna (Water flea) - 1,4 mg/l

- 48 h

invertebrates Remarks: (ECHA)

Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata - 0,16 mg/l -

96 h

Remarks: (ECHA)

Toxicity to bacteria EC50 - Bacteria - 580 mg/l - 3 h

(OECD Test Guideline 209)

Toxicity to daphnia and other aquatic

semi-static test NOEC - Daphnia magna (Water flea) - 0,065

and other aquatic mg/l - 21 d invertebrates(Chronic Remarks: (ECHA)

toxicity)

semi-static test EC50 - Daphnia magna (Water flea) - 0,46 mg/l

- 21 d

Remarks: (ECHA)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

Sigma- P5412 Page 11 of 14

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1673 IMDG: 1673 IATA: 1673

14.2 UN proper shipping name

ADR/RID: PHENYLENEDIAMINES IMDG: PHENYLENEDIAMINES IATA: Phenylenediamines

14.3 Transport hazard class(es)

ADR/RID: 6.1 IMDG: 6.1 IATA: 6.1

14.4 Packaging group

ADR/RID: III IMDG: III IATA: III

14.5 Environmental hazards

ADR/RID: yes IMDG Marine pollutant: yes IATA: no

14.6 Special precautions for user

Tunnel restriction code : (E)

Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

National legislation

Seveso III: Directive 2012/18/EU of the H2 ACUTE TOXIC European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E1 ENVIRONMENTAL HAZARDS

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements

H301 Toxic if swallowed.

Sigma- P5412 Page 12 of 14

H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM -American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. -Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the mixture		Classification procedure:
Acute Tox.3	H301	Calculation method
Eye Irrit.2	H319	Calculation method
Skin Sens.1	H317	Calculation method
Muta.2	H341	Calculation method
Carc.2	H351	Calculation method

Sigma- P5412 Page 13 of 14

Aquatic Acute1 H400 Calculation method Aquatic Chronic1 H410 Calculation method

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.



Sigma- P5412 Page 14 of 14